



## eicó GOLVOLJA IMPREGNATING FLOOR OIL

Solvent free, impregnating oil. All natural ingredients. Quick and easy application very durable and stain resistant.

### CHARACTERISTICS

eicó GOLVOLJA is a solvent free unique blend of renewable pure natural oils. It impregnates, nourishes and penetrates deep into the pores of the wood. It fills up the pores without shrinkage during drying. 2nd coat can be applied after 24 hours and can be polished. A surface treated with eicó.

GOLVOLJA remains anti-static and breathing and preserves the matt look of oiled wood, while providing good resistance against water, dirt and stains.

### APPLICATION

eicó GOLVOLJA is used for impregnating, nourishing and protecting parquet and wooden floors and other interior wooden surfaces.

CLASSIFICATION > 99% natural ingredients.

### INGREDIENTS

Oil : contains a proprietary blend of natural vegetable oils.

Additives : essential oils and Cobalt-soap dryer.

100% Full Solid. 100% Solvent free. 100% Water free. 100% Natural.

### PROPERTIES

Liquid eicó GOLVOLJA.

Density : 0,92 - 0,94 kg/dm<sup>3</sup>

Viscosity : running liquid

Solid Content : 100 %

VOC content : 0 g/l

Dried eicó GOLVOLJA

Matt, anti-slip and very resistant against water, dirt and stains.

2nd coat polishable to a satin finish.

### SYSTEM

One treatment of eicó GOLVOLJA is sufficient. Apply 2nd coat for finishing and polishing.

## APPLICATION

Conditions: Surface temperature should be +10°C and/or a relative humidity above 80%. eicó.

GOLVOLJA requires oxygen to cure. Provide sufficient ventilation during application and curing of the oil.

Thinning: eicó GOLVOLJA is ready to use, do not thin down. Only very hard, poor absorbing surfaces may require a maximum of 10% of gum turpentine thinning.

Substrate: the substrate shall be evenly sanded (last sanding with P120 grain) and shall be clean, dry and free of wax, grease, dust and dirt.

Tools: eicó GOLVOLJA can be applied with a roller, spatula or bristle. Cloths, rollers and sponges with eicó GOLVOLJA shall be left unfolded, in free air in order to avoid self-ignition.

Application: Apply eicó GOLVOLJA superfluously and leave to penetrate for about 20 minutes, successively rub-in the oil with a pad to aid penetration and smooth the surface. As a last step, all superfluous oil on the floor that has not penetrated shall be removed by wiping off with cotton cloths. No glossy/shiny puddles or films of oil shall remain after wiping off with cotton cloths. Change cloth regularly.

## DRYING

Drying times at 20°C, 65 % RH and sufficient ventilation.

Dry to carefully walk on : direct (careful not to leave marks).

Dry to carefully use : after 24-48 hours.

Fully cured : after 7-10 days.

## USAGE

15 - 30 m<sup>2</sup> per litre, depending on substrate and application.

## MAINTENANCE

Clean regularly with a mild detergent. Re-apply eicó GOLVOLJA when necessary, after thorough cleaning.

## SHELF LIFE

Store dry in a cool place in well closed original container. Shelf Life 2 years after production. Limited shelf life once opened.

## WARNING

**eicó GOLVOLJA contains drying oil. Cloths with drying oil can self-ignite by overheating: Let cloths dry unfolded or soak with water.**