



## Helmatt

eicó Helmatt is a high quality waterborne paint for interior walls and ceilings. It dries to a non-yellowing, completely flat finish and has excellent colour retention. Due to high solid contents, it covers very well which also gives extremely high filling and hiding power making it also suitable for use as a base coat. It has good resistance against normal household chemicals and is also lightly washable. eicó Helmatt is NFE0 and solvent free with an extremely low rating (VOC  $\leq$  0.1%) making this an exceptionally environmentally friendly paint. EU limit for this product (Cat A/a): 75g/ltr (2007)/30g/ltr (2010). This product contains max.1g/litre VOC. The paint has also been tested to comply with the Asthma and Allergy Foundation in Sweden.

### AREA OF USE

Interior: walls, ceilings.

Substrates: concrete, cement, rendered plaster, plasterboard, lining paper, glass fibre, and particleboard.

### APPLICATION

The surface must be stable, dry and free of dust, sand, loose old paint, dirt, grease and oil. On rough surfaces, it may be necessary to dilute the paint by about 10% with fresh water. Use only where application and drying can proceed at temperatures above 5°C, preferably 10°C or more) with relative humidity below 85%. Surface temperature should be between 5–35°C.

### TECHNICAL INFORMATION

Gloss level: 4 (Helmatt)

Binder: Styrolacrylic

Solvent: Fresh Water

Coverage: 8 – 10 m<sup>2</sup>/Litre

Cleaning of tools: Water

Volume Solid: 39%

Drying time: 2 - 3 hours (Touch dry)

Recoating time: Min. 4-5 hours (Depending upon temperature & relative humidity)

### SAFETY

Handle with care. Consult Material Safety Data Sheet and follow all local or national regulations. Avoid inhalation and contact with skin and eyes. Do not swallow. Take precautions against possible risks of fire and explosion, as well as protection of the environment. Apply only in well-ventilated areas. Do not paint if the surface is colder than +5°C. Once opened, keep can tightly sealed. Wipe away as much paint as possible from painting tools before cleaning with water. Liquid paint waste must not be poured down the drain – dispose of it according to local regulations. Hand in empty cans to your nearest recycling depot. KEEP AWAY FROM CHILDREN.

The logo for eicó, featuring the word "eicó" in a white, lowercase, sans-serif font with a diacritical accent over the 'o', set against a dark navy blue rectangular background.

eicó **paints Limited**

861-863, Fulham Road, London, SW6 5HP Tel: +44 (0)845 073 9432 Fax: +44 20 7384 3723  
Email: [info@eico.co.uk](mailto:info@eico.co.uk) Web: [www.eico.co.uk](http://www.eico.co.uk)